

# Indoor Lighting LED Linear Fixtures



## STA Series Standard Linear Fixture

### FEATURES

- Available in 4 ft and 8 ft
- Universal line voltage internal driver
- Durable quality
- Connectors designed for fast installation
- Connects in a series (up to 200 watts)
- Does not require a ballast
- ETL Listed
- Efficiency up to 120 lumens per watt
- Install everywhere wall or ceiling

### BENEFITS

- Lasts 50x longer than incandescent
- Uses half the energy of fluorescent tubes
- Improves light uniformity
- 5 year warranty

## SPECIFICATIONS

Item#/SKU	Model#	Size	Watts	Lumens	Qualified	CCT	Lens	Input Voltage	Operating Temperature	Beam Angle	Lifespan
<b>HD Series – High Definition Linear Fixtures</b>											
105908	105908	4'	30W	3000	ETL	5000K	Frosted	100-277V	-4F/113F	120°	50,000 hrs
105916	105916	4'	30W	3000	ETL	6000K	Frosted	100-277V	-4F/113F	120°	50,000 hrs
<b>AC Series – Standard Linear Fixtures</b>											
102350-1	102350	4'	22W	2420	ETL & DLC	5000K	Frosted	85-277V	10F/122F	120°	50,000 hrs
102350-2	102350	4'	22W	2640	ETL & DLC	5000K	Clear	85-277V	10F/122F	120°	50,000 hrs
101642	101642	4'	22W	2640	ETL	6500K	Clear	85-277V	10F/122F	120°	50,000 hrs
101642-1	101642-1	4'	22W	2640	ETL	6500K	Striped	85-277V	10F/122F	180°	50,000 hrs
102970	102970	4'	28W	3360	ETL	6500K	Clear	85-277V	10F/122F	120°	50,000 hrs
102970-1	102970-1	4'	28W	3360	ETL	6500K	Striped	85-277V	10F/122F	180°	50,000 hrs
102970-2	104315	4'	28W	3360	ETL & DLC	5000K	Clear	85-277V	10F/122F	120°	50,000 hrs
102970-4	104315	4'	28W	3080	ETL & DLC	5000K	Frosted	85-277V	10F/122F	120°	50,000 hrs
102343	102343	8'	44W	5280	ETL	6500K	Clear	85-277V	10F/122F	120°	50,000 hrs
102343-1	102343-1	8'	44W	5280	ETL	6500K	Striped	85-277V	10F/122F	180°	50,000 hrs
102343-2	102343-2	8'	44W	5280	ETL	6500K	Frosted	85-277V	10F/122F	120°	50,000 hrs
102814	102814	8'	60W	7320	ETL	6500K	Clear	85-277V	10F/122F	120°	50,000 hrs
102814-1	102814-1	8'	60W	7320	ETL	6500K	Striped	85-277V	10F/122F	180°	50,000 hrs

Available in 4000K on custom order